


Double Disc Miniature Coupling

Body Material: Aluminum Alloy

Disc Material: Stainless Steel



型号	成型孔尺寸		ΦD	L	W	L1	L2	M	拧紧力矩 (N.m)
	dmin	dmax							
26	5	10	26	35	2.5	11.5	7.0	M3	1.5
34	8	14	34	45	3.1	14.1	10.6	M4	1.5
39	10	16	39	49	4.1	15.0	10.8	M4	2.5
44	11	19	44	50	4.5	15.0	11.0	M4	2.5
56	14	24	56	63	5.0	20.0	13.0	M5	7.0
68	19	35	68	74	6.0	24.0	14.0	M6	12
82	24	40	82	98	8.0	30.0	22.0	M8	16

型号	额定扭矩 (N.m)	最大扭矩 (N.m)	最高转速 (rpm)	惯性力矩 (kg.m ²)	静态扭矩刚性 (N.m/rad)	径向偏差 (mm)	角向偏差 (°)	轴向偏差 (mm)	重量 (g)
26	1.4	2.8	10000	3.3×10^{-6}	950	0.04	1.5	±0.4	34
34	2.8	5.6	10000	8.9×10^{-6}	1960	0.04	1.5	±0.4	70
39	5.8	11.6	10000	2.4×10^{-5}	4500	0.04	1.5	±0.4	118
44	8.7	17.4	10000	3.2×10^{-5}	5100	0.04	1.5	±0.4	142
56	25	50	10000	1.1×10^{-4}	10500	0.04	1.5	±0.4	296
68	55	110	10000	2.8×10^{-4}	18500	0.04	1.5	±0.4	544
82	80	160	10000	1.0×10^{-3}	21800	0.04	1.5	±0.4	1020

说明：惯性力矩和重量按最大孔径计算