


Single Disc Miniature Coupling

Body Material: Aluminum Alloy

Disc Material: Stainless Steel



型号	成穿孔尺寸		ΦD	L	W	L1	M	拧紧力矩 (N.m)
	dmin	dmax						
26	5	10	26	25.5	2.5	11.5	M3	1.5
34	8	14	34	31.3	3.1	14.1	M4	1.5
39	10	16	39	34.1	4.1	15.0	M4	2.5
44	11	19	44	34.5	4.5	15.0	M4	2.5
56	14	24	56	45.0	5.0	20.0	M5	7.0
68	19	35	68	54.0	6.0	24.0	M6	12
82	24	40	62	68.0	8.0	30.0	M8	16

型号	额定扭矩 (N.m)	最大扭矩 (N.m)	最高转速 (rpm)	惯性力矩 (kg.m ²)	静态扭矩刚性 (N.m/rad)	角向偏差 (°)	轴向偏差 (mm)	重量 (g)
26	1.4	2.8	10000	1.8×10^{-6}	690	1.0	±0.2	24
34	2.8	5.6	10000	7.2×10^{-6}	1650	1.0	±0.2	46
39	5.8	11.6	10000	1.8×10^{-5}	2500	1.0	±0.2	78
44	8.7	17.4	10000	2.5×10^{-5}	2900	1.0	±0.2	96
56	25	50	10000	1.0×10^{-4}	8400	1.0	±0.2	206
68	55	110	10000	1.9×10^{-4}	11500	1.0	±0.2	366
82	80	160	10000	7.0×10^{-4}	14550	1.0	±0.2	710

说明：惯性力矩和重量按最大孔径计算

Add.: No. 8 Jinhua Road, Chengdu 610021, China

Tel: +86-28-65998825 Fax: +86-28-84862968

www.cdleno.com

Email: sales@cdleno.com